

MATERIAL SAFETY DATA SHEET

PRO SEAL® COARSE

Product ID: 1 Trade Name: **PRO SEAL® COARSE** Revision Date: January 01, 2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: PRO SEAL® COARSE Chemical Family: Cellulose
Product Use: Oil well drilling fluid additive. Lost circulation material.
Emergency Telephone (24 hr.): (888) 862-7177

Supplied by: Professional Fluid Services, LLC P.O.BOX 80293 LAFAYETTE, LOUISIANA. 70598

Telephone Number: (888) 862-7177
Contact Person: ROBERT COPELAND

Revision Number: 1

HMIS Rating Health: 1 * Flammability: 1 Physical Hazard: 0 PPE: E

HMIS Key: 4=Severe, 3=Serious, 2=Moderate, 1 =Slight, O=Minimal Hazard. *Chronic effects - See Section 11. See Section 8 for Personal Protective Equipment recommendations.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS NO:	WT%	Ingredient Comments
Cellulose	9004-34-6	99-100	N/A
Silica, crystalline quartz	1408-60-7	0.1-1	N/A

3. HAZARDS IDENTIFICATION

Emergency Overview: Caution! May cause eye, skin, and respiratory tract irritation. Long-term inhalation of particulates may cause lung damage. Cancer hazard. Contains crystalline silica which may cause lung cancer.

Canadian Regulations: WHMIS Class: D2A

Physical Odor: Mild (Very Faint) **Color:** Tan **State:** Powder, Dust

Potential Health Effects: Acute Effects

Eye Contact: May cause mechanical irritation
Skin Contact: May cause mechanical irritation. Long-term contact can cause skin dryness.
Inhalation: May cause mechanical irritation.
Ingestion: May cause gastric distress, nausea and vomiting if ingested.
Carcinogenicity & Chronic Effects: See Section 11 - Toxicological Information.
Routes of Exposure: Eyes. Dermal (skin) contact. Inhalation.
Target Organs: Eyes-Skin. Respiratory System.